

Data sheet - V.07.23

VP-P

Vacuum Press Professional



GLOBAL
VACUUM PRESSES

VP-P

Vacuum Press Professional

Model	VP-P-2514 VP-P-2516	VP-P-3114 VP-P-3116	VP-P-3714 VP-P-3716
Press area	2560 x 1420 mm 2560 x 1620 mm	3160 x 1420 mm 3160 x 1620 mm	3760 x 1420 mm 3760 x 1620 mm
Operation	Manual operation Vacuum switch AUTOMATIC / OFF / CONTINUOUS Vacuum control valve		
Vacuum pump	40 m ³ /h	40 m ³ /h	40 m ³ /h
Max. pressure	8.5 t/m ² = 150 mbar abs. (85% Vacuum)		
Membrane	NR / SI	NR / SI	NR / SI
Work top	18 mm wear-resistant HPL compact board Grid line raster for even air evacuation Working height 900 mm		
Supports	4 x Industrial swivel wheels, 2 with break		
Elec. connection	220/400V, 3~, 50/60 Hz		
Max. power	1.25 kW	1.25 kW	1.25 kW
Dimensions	2720 x 1530 x 980 mm	3320 x 1530 x 980 mm	3920 x 1530 x 980 mm
Weight	375 kg 385 kg	420 kg 430 kg	475 kg 480 kg
Certification	CE – Declaration of conformity CO – Certificate of origin (on request)		

Technical information may differ slightly

NR = Natural rubber | SI = Silicone membrane

* Optional features

- 40 m³/h oil-lubricated vacuum pump
- High volume silicone membrane
- 300 liter vacuum tank with T-ball valve
- Top frame with vacuum cups for fast closing & opening
- External vacuum connection
- Digital vacuum switch
- Cover 140 and 160 cm